



RAVENOL Super HD 30

Kategorie: Passenger car motor oil

Artikelnummer: 1113300

Viscosity: 30

Specification: API CD, API SF

Oil type: Mineral

Recommendation: CCMC G4, MB 227.0, MIL-L-2104 D, MIL-L-46152 B

Application: Passenger car, Truck, Agricultural machinery, Hobby and garden



RAVENOL Super HD 30 is mineral mono grade engine oil for passenger car gasoline and diesel engines with and without turbocharging, and is also suitable for commercial vehicle engines and vans under light loads which require this grade of oil. Designed to minimize friction and wear, the formulation ensures year round high lubricity throughout all operating conditions. Extended oil drain capability where recommended by the vehicle manufacturer.

Application Note

RAVENOL Super HD 30 is suitable for both gasoline and diesel engines in cars, van and commercial vehicles which require this grade of engine oil.

Characteristics

- Corrosion protection
- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge

1L | 1113300-001

4L | 1113300-004

5L | 1113300-005

10L | 1113300-010

20L | 1113300-020

20L | 1113300-B20

60L | 1113300-060

208L | 1113300-208

1000L | 1113300-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	876,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm²/s	12,1	DIN 51562-1
Viscosity at 40 °C	mm²/s	103,3	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Pourpoint	°C	-27	DIN ISO 3016
Flashpoint	°C	248	DIN EN ISO 2592
tbn	mg KOH/g	7,2	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.