



RAVENOL SCOOTER 4-Takt Fullsynth.



1L | 1151155-001

Kategorie: 4 stroke engine oil

Artikelnummer: 1151155

Specification: API SN Plus, API SP, SAE 5W-40

Oil type: Full synthetic

Recommendation: Aprilia, Arctic Cat, Argo, Bombardier, Dinli, Honda, Kawasaki, Peugeot, Piaggio, Polaris, Suzuki, Yamaha

Application: Motorcycle

RAVENOL SCOOTER 4-Takt Fullsynth. is a full synthetic high quality green colored engine oil for 4-stroke small engines. A specially designed additive package and a formulation with special ingredients for a high viscosity index ensure for a clean engine and clean inlet and exhaust systems and thus proper lubrication and wear protection.

RAVENOL SCOOTER 4-Takt Fullsynth. due to its special additives and the selection of base oils and its viscosity an energy-saving operation of engines. Due to its special active ingredients ensures

RAVENOL SCOOTER 4-Takt Fullsynth. for a cleaner engine and clean inlet and exhaust systems.

RAVENOL SCOOTER 4-Takt Fullsynth. is the product for optimal life of the machine.

RAVENOL SCOOTER 4-Takt Fullsynth. ensures excellent cold start performance for optimum lubrication safety in the cold run phase.

Application Note

RAVENOL SCOOTER 4-Takt Fullsynth. is for use in 4 -Stroke engines.

Characteristics

- High wear protection
- Fuel savings through smooth running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long life due to high oxidation stability
- Excellent cold start behavior
- Very good viscosity-temperature behavior
- Low evaporation tendency

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	847,0	EN ISO 12185
Colour		grün	VISUELL
Viscosity at 100 °C	mm ² /s	13,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	78,2	DIN 51562-1
Viscosity Index VI		173	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,91	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	5480	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	25.000	ASTM D4684
Pourpoint	°C	-39	DIN ISO 3016
Noack Volatility	% M/M	7,4	ASTM D5800
Flashpoint	°C	240	DIN EN ISO 2592
tbn	mg KOH/g	11,8	ASTM D2896
Sulphated Ash	%wt.	1,19	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.