



RAVENOL Selfmix 2T

Kategorie: 2 stroke engine oil

Artikelnummer: 1153100

Specification: API TC, ISO L-EGB, NMMA TC-W

Oil type: Mineral

Approvals: JASO FB (M049RAV155)

Recommendation: Dolmar, Hitachi, Husqvarna, Jonsered, Makita, Maruyama, McCulloch, Oleo-Mac, Oregon, Partner, Poulan, Ryobi, Stihl

Application: Motorcycle, Marine, Hobby and garden



RAVENOL Selfmix 2T is a premixed mineral lubricant which meets the exacting demands of two-stroke engines. It effectively prevents the accumulation of carbon deposits in the piston, the combustion chambers and the exhaust ports, and is formulated to avoid contamination of spark plugs and corrosion damage to drive mechanism components.

Application Note

RAVENOL Selfmix 2T is specially designed for universal use in motorcycles which have separate lubrication and self-mixing systems. When used in separate lubrication systems this product will ensure optimal lubrication and minimizes smoke to help protect the environment. It is suitable for air-cooled as well as water-cooled two-stroke gasoline engines in motorcycles, mopeds and scooters, as well as for other equipment such as lawnmowers etc.

Characteristics

- Excellent corrosion protection
- Excellent oxidation stability
- Very high wear protection
- Environmentally friendly with low smoke formulation
- Low coking capabilities
- Formulated for universal use

0.1L | 1153100-100

1L | 1153100-001

1L | 1153100-D01

4L | 1153100-004

10L | 1153100-010

20L | 1153100-020

20L | 1153100-B20

60L | 1153100-060

208L | 1153100-208

1000L | 1153100-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	872,0	EN ISO 12185
Colour		rot	VISUELL
Viscosity at 100 °C	mm²/s	9,0	DIN 51562-1
Viscosity at 40 °C	mm²/s	66,4	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	178	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.