



RAVENOL Outboardoel 4T SAE 25W-40



1L | 1153207-001

4L | 1153207-004

10L | 1153207-010

20L | 1153207-020

20L | 1153207-B20

60L | 1153207-060

208L | 1153207-208

Kategorie: 4 stroke engine oil

Artikelnummer: 1153207

Viscosity: 25W-40

Specification: API SM, NMMA FC-W, NMMA FC-W (CAT)

Oil type: Mineral

Approvals: NMMA FC-W CAT, FC-43517X

Recommendation: Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha

Application: Marine

RAVENOL Outboardoel 4T SAE 25W-40 is a mineral engine oil with a special formulation for 4-stroke outboard engines with injection according to NMMA FC-W and NMMA FC-W (CAT).

RAVENOL Outboardoel 4T SAE 25W-40 offers perfect lubrication and wear protection through special low-ash additives and excellent corrosion protection.

RAVENOL Outboardoel 4T SAE 25W-40 is blue colored high performance 4-stroke motor oil.

RAVENOL Outboardoel 4T SAE 25W-40 is released and thus meets the requirements of the National Marine Manufacturers Association NMMA FC-W (CAT) for use in engines with catalysts.

Application Note

RAVENOL Outboardoel 4T SAE 25W-40 can be used in all outboard motors according to the engine manufacturer's specifications, for which oil is recommended according to FC-W and FC-W (CAT).

RAVENOL Outboardoel 4T SAE 25W-40 can also be used for engines operating in seawater.

RAVENOL Outboardoel 4T SAE 25W-40 meets the requirements from Yamaha 115 General Performance Engine Test for 4-stroke outboard motors.

Follow the manufacturer's recommendations.

Characteristics

- Perfect lubrication of all engine parts
- A strong cleaning effect and a residue-free combustion without deposits
- Good cold start properties
- A very high-wear, oxidation and corrosion protection
- Excellent shear stability
- Corrosion protection in all oil-wetted engine parts
- An adhesive, pressure-and temperature-resistant oil film

- Suitable for Catalysts

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
tbn	mg KOH/g	7,2	ASTM D2896
Viscosity at 100 °C	mm²/s	13,6	DIN 51562-1
Viscosity at 40 °C	mm²/s	120,7	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Density at 20 °C	kg/m³	878,6	EN ISO 12185
Flashpoint	°C	262	DIN EN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.