



# RAVENOL LHM PLUS Fluid

**Kategorie:** Car hydraulic oil

**Artikelnummer:** 1181110

**Specification:** ISO 7308, PSA Standard B 71 2710

**Oil type:** Semi-synthetic

**Application:** Passenger car



**RAVENOL LHM PLUS Fluid** is special semisynthetic hydraulic fluid especially designed for use in vehicles of the PSA group (Citroen, Peugeot).

Due to its special formulation **RAVENOL LHM PLUS Fluid** has significantly improved low temperature viscosity and fulfils the PSA approval specification.

## Application Note

**RAVENOL LHM PLUS Fluid** is used in vehicles with appropriately marked fluid reservoir for the hydraulic operation or support of braking, steering and suspension functions.

**RAVENOL LHM PLUS Fluid** is miscible with earlier LHM fluids.

## Characteristics

- A low pour point.
- Excellent viscosity behavior at low temperatures.
- An extremely high viscosity index.
- Low viscosity at low temperatures.
- Neutral behavior towards sealing materials.

**1L | 1181110-001**

**4L | 1181110-004**

**10L | 1181110-010**

**20L | 1181110-020**

**20L | 1181110-B20**

**60L | 1181110-060**

**208L | 1181110-208**

**1000L | 1181110-700**

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	831,0	EN ISO 12185
Colour		klar, grün	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	7,2	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	25,3	DIN 51562-1
Viscosity Index VI		273	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	3460	ASTM D2983
Viscosity at -40 °C		2600	ASTM D445
Pourpoint	°C	-72	DIN ISO 3016
Flashpoint	°C	172	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.