



# RAVENOL Feinmechanik-Oel

**Kategorie:** Industrial oil

**Artikelnummer:** 1350360

**Oil type:** Mineral

**Application:** Agricultural machinery, Industry, Hobby and garden



**RAVENOL Feinmechanik-Oel** is a multi-purpose, universal general purpose lubricant, resin- and acid-free and therefore particularly suitable for the lubrication of high technology precision mechanics.

**RAVENOL Feinmechanik-Oel** is dewaxed and treated in the hydrofinishing process and oxidizes itself only very slowly under UV and oxygen influence.

**RAVENOL Feinmechanik-Oel** is also suitable for very fast-acting mechanism.

## Application Note

**RAVENOL Feinmechanik-Oel** can be used as a universal general purpose oil both in the home and out for bicycles, sewing machines, household and office equipment, locks, tools, cars, motorcycles, hobby work etc. and anywhere that this type of multi-purpose oil is required.

## Characteristics

- Free from resin and acid, therefore no binding of deposits
- Low sulfur content
- Non-aging oil with a good viscosity-temperature behavior
- Good anticorrosive characteristics
- Very good wear reduction
- Easy handling and sprayability
- Wear protection and pressure absorption capacity

**0.1L | 1350360-100**

**1L | 1350360-001**

**5L | 1350360-005**

**10L | 1350360-010**

**20L | 1350360-020**

**20L | 1350360-B20**

**60L | 1350360-060**

**208L | 1350360-208**

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	834,0	EN ISO 12185
Colour		hell	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	6,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	32,1	DIN 51562-1
Viscosity Index VI		135	DIN ISO 2909
Pourpoint	°C	-18	DIN ISO 3016
Flashpoint	°C	190	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.