



RAVENOL TTC Premix -40°C Protect C11

Kategorie: Radiator antifreeze

Artikelnummer: 1410105

Recommendation: AFNOR R15-601, ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4985, ASTM D6210 Type 1-FF, BS 6580 (GB), Chrysler MS-7170, CUNA NC 956-16 (Italien), Fiat 9.55523, Fiat PARAFUO 11, Ford WSS-M97B51-A1, IVECO 18-1830, JIS K 2234 (Japan), MAN 324 NF, O Norm V 5123 (Österreich), SAE J1034, Suzuki, UNE 25-361 (Spanien), VW TL 774-C (entspricht G11)



RAVENOL TTC Trad. Techn. Coolant Premix -40°C is a ready to use, prediluted eco-friendly 1.2- Ethanediol (monoethylene glycol) based nitrite, amine and phosphate-free coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. The product is formulated as a long-term coolant based on a proven inhibitor development.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why manufacturers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL TTC Trad. Techn. Coolant Premix -40°C protects the cooling system from rust, frost, and in summer, from overheating.

Application Note

RAVENOL TTC Trad. Techn. Coolant Premix -40°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL TTC Trad. Techn. Coolant Premix -40°C** to radiator to fill line.

Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastome

- 1.5L | 1410105-150
- 5L | 1410105-005
- 20L | 1410105-020
- 20L | 1410105-B20
- 60L | 1410105-060
- 208L | 1410105-208
- 1000L | 1410105-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	1080,0	EN ISO 12185
Colour		gelb-grün fluoreszent	VISUELL
pH - value at 20 °C		7,8	ASTM D1287
Freezing point	°C	-40	ASTM D1177

All indicated data are approximate values and are subject to the commercial fluctuations.